

SAFECO BRAND GFT-02-600

2" 600# ANSI RAISED-FACE
FABRICATED STEEL NATURAL GAS FILTER



FILTER ELEMENT

Number of Elements : One

Inner Shield : 22 Ga. CS Perforated
Outer Shield : 18 Ga. CS Perforated
End Caps : 22 Ga CS EP
MIN Collapse : 25 PSID

Cellulose Part # : 020040170-10C
Retention : 10 Microns @ 99%

Polyester Part # : 020040170-5P
Retention : 5 Microns @ 99%

CONSTRUCTION MATERIALS

Closure Type : Bolted
Davit Arm : 1" CR CARBON STEEL
Closure Bolts : SA-193 GR B-7
Closure Cap : SA-105
Gasket Size : 6" 600# RING
Gasket Mat'l : 304 SS / GRAPHITE
Closure Hub : SA-105
Body : SA-106 GR B
Bottom : SA-234 GR WPB
Inlet : SA-105 / SA-106 GR B
Outlet : SA-105 / SA-106 GR B
Drain : SA-105
High-side DP Tap : SA-105
Low-side DP Tap : SA-105
Leg Supports : N / A
Skirt : N / A
Base Plate : N / A
Net Weight : 292 lbs

SCHEDULE OF OPENINGS

Inlet : 2" 600# ANSI RF
Outlet : 2" 600# ANSI RF
Drain : 1/2" F-NPT, w/ Plug
Vent : 1/4" F-NPT, w/ Plug
High-side DP Tap : 1/4" F-NPT, w/ Plug
Low-side DP Tap : 1/4" F-NPT, w/ Plug

DESIGN

Pressure Class : ASME / ANSI 600
Max Pressure : 1480 psig
Max Temperature : 100 Degrees F
Corrosion Allowance : None
CODE Stamped : Available

TESTING

Hydrostatic Test : 2250 PSIG
Pneumatic Test : 80 PSIG
Radiography : Available RT-1

COATING

2 mils Oxidating Primer,
Sand Blasting and
Other Coatings Available

